



SITE SPREADER[®]

15 Ton Open Top Site Spreader Model SSOT 1516

Spreader for Cement, flyash, quicklime and other dry, flowable materials



SSOT 1516 Standard Features

- Tractor drawn
- Up to 15 ton capacity
- 7 gauge pan, 11 ga hopper, fully welded
- 30" hardened D667KC conveyor chain
- PTO conveyor drive (1000 rpm, 21 spline)
- Manual rear metering gate
- Top loading
- 8 ft [2.43 m] Hydraulic spreading auger w/ dust curtains
- Hydraulic valve (open/closed center tractor)
- Clevis hitch
- Walking beam suspension
- 21.5L x 16.1 (14 ply) tires
- Spread rate: up to 30 lb/yd² @ 2mph, 60 lb/yd² @ 1 mph
- Calibration kit

Dimensions:	
Hopper length:	16 ft
Hopper width:	74 in
Total length:	24 ft
Total height:	78 in
Total width:	106 in
Volume:	225 ft ³
Approx. weight:	5,700 lbs

Popular Options

- Hydraulic rear metering gate
- Grate to hold bulk bags while filling

Stoltz Mfg., LLC

121 Morgan Way, PO Box 527
Morgantown, PA 19543 USA

+610-286-5146

800-843-8731

www.stoltzmf.com