



# SITE SPREADER<sup>®</sup>

## 15 Ton Pull-Type Site Spreader Model SS 1516

Spreader for Cement, flyash, quicklime and other dry, flowable materials



Spreader with high capacity filter can



Spreader with popup filters on roof



Versatile and maneuverable



Limited space operation

### SS 1516 Standard Features

- Tractor drawn
- 15 ton "half-tanker" capacity
- Sealed, reinforced 7-ga steel hopper
- 30" hardened D667KC conveyor chain
- PTO conveyor drive (1000 rpm, 21 spline)
- Hydraulic rear metering gate
- 4" Pneumatic fill
- High flow low pressure relief valve
- High capacity filter can
- 8 ft [2.43 m] Hydraulic spreading auger w/ dust curtains
- Side access panels
- Walking beam suspension
- 21.5L x 16.1 (14 ply) tires
- Spread rate: up to 60 lb/yd<sup>2</sup> @ 2mph, 120 lb/yd<sup>2</sup> @ 1 mph

### Popular Options

- 10 ft [3.04m] or 12 ft [3.65m] Spreading auger
- 24" Manway on roof for top-loading
- Popup filter bags on roof (instead of filter can)
- Plug to tractor hydraulic drive (manual control)

Dimensions:	
Hopper length:	16 ft [4877 mm]
Hopper width:	86 in [2184]
Total length:	26 ft [7925]
Total height:	125 in [3175]
Total width:	102 in [2693]
Useable volume:	475 ft <sup>3</sup> [13.45 m <sup>3</sup> ]

### Stoltz Mfg., LLC

121 Morgan Way, PO Box 527

Morgantown, PA 19543 USA

+610-286-5146

800-843-8731

[www.stoltzmf.com](http://www.stoltzmf.com)