



SITE SPREADER[®]

5th Wheel Pull-Type Site Spreader Model SST5 1516/2720

Spreader for Cement, flyash, quicklime and other dry, flowable materials



Spreader with high capacity filter can



Fill directly from the bulk tanker



Tow with any road tractor



Automatic rate controller

Standard Features

- Mounted on 5th wheel trailer
- 73 HP Deutz diesel engine
- Automatic or manual rate controller
- 15 ton "half-tanker" or 27 ton full tanker capacity
- Sealed, reinforced 7-ga steel hopper
- 30" [762 mm] hardened D667KC conveyor chain
- Hi-torque, hi-speed hydraulics
- Hydraulic rear metering gate
- 4" Pneumatic fill
- High flow low pressure relief valve
- High capacity filter can
- 8 ft [2.43 m] Hydraulic spreading auger w/ dust curtains
- Side access panels
- Spread rate: up to 120 lb/yd² @ 2mph, 80 lb/yd² @ 3 mph
[65 kg/m³ @ 3.2 kph, 43 kg/m³ @ 4.8 kph]

Popular Options

- 10 ft [3.04m] or 12 ft [3.65m] Spreading auger
- 24" Manway on roof for top-loading
- Popup filter bags on roof (instead of filter can)
- Vulcan (6 load cell) digital scale

Dimensions	SST5 1516	SST5 2720
Volume, ft ³ [m ³]	475 [13.5]	741 [20.9]
Length, ft [mm]	30.5 [9296]	34.5 [10516]
Width, in [mm]	102 [2591]	102 [2591]
Height, in [mm]	122 [3098]	124 [3140]

Stoltz Mfg., LLC

121 Morgan Way, PO Box 527
Morgantown, PA 19543 USA

+610-286-5146

800-843-8731

www.stoltzmf.com