



SITE SPREADER[®]

8 Ton Open Top Site Spreader Model SSOT 8010

Spreader for Cement, flyash, quicklime and other dry, flowable materials



SSOT 8010 Standard Features

- Tractor drawn
- Up to 8 ton capacity
- 7 gauge pan, 11 ga hopper, fully welded
- 24" hardened D667X conveyor chain
- PTO conveyor drive (540 rpm)
- Manual rear metering gate
- Top loading
- 8 ft [2.43 m] Hydraulic spreading auger w/ dust curtains
- Hydraulic valve (open/closed center tractor)
- Clevis hitch
- Walking beam suspension
- 19L x 16.1 (10 ply) tires
- Spread rate: up to 12 lb/yd² @ 2mph, 24 lb/yd² @ 1 mph
- Calibration kit

Dimensions:	
Hopper length:	10 ft
Hopper width:	78 in
Total length:	18 ft
Total height:	87 in
Total width:	94 in
Volume:	177 ft ³
Approx. weight:	4,500 lbs

Popular Options

- Hydraulic rear metering gate
- Grate to hold bulk bags while filling

Stoltz Mfg., LLC

121 Morgan Way, PO Box 527
Morgantown, PA 19543 USA

+610-286-5146

800-843-8731

www.stoltzmfg.com